5210-H-15-A

Recessed Automatic Roll Paper Towel Dispenser and Waste Receptacle

Dispenses rolls 8" or 9" wide (205-230 mm) 800 feet long in preset lengths: $2^1/2$ ", 4" or 5" per stroke (65, 100 or 125 mm).

Removable waste receptacle is 15 gallons (57 L).

Wall Opening:

15 3/4" X 54 1/2" X 10 1/4" (400 x 1384 x 260 mm)

Suggested Mounting Height:

20" from bottom of unit to floor; barrier-free, 6" (510 & 150 mm).

Options:

5210-H-15-A - Battery-Operated **5210-H-15-AC** - 110-240 VAC

Not Shown:


5210-H-15-A-S6 - Model 5210-H-15-A with stainless steel collar for semi-recessing in 4" (102 mm) walls.

5210-H-15-A-S9 - Model 5210-H-15-A with stainless steel collar for surface mounting.

5210-H-15-AC-S6 - Model 5210-H-15-A with stainless steel collar for semi-recessing in 4" (102 mm) walls.

5210-H-15-AC-S9 - Model 5210-H-15-A with stainless steel collar for surface mounting.





5210-H-15-A

5210-P-14-A

Semi-Recessed Automatic Roll Paper Towel Dispenser and Waste Receptacle

Dispenses rolls 8" or 9" wide (205-230 mm) 800 feet long in preset lengths: $2^{1}/z$ ", 4" or 5" per stroke (65, 100 or 125 mm). Removable waste receptacle is 14 gallons (53 L)..

Wall Opening: 15 3/4" x 54 1/2" x 41/4" (400 x 1384 x 110 mm)

Suggested Mounting Height:

16" from bottom of unit to floor; barrier-free, barrier-free wheelchair accessible side reach, 4" (405 & 102 mm).

Options:

5210-P-14-A - Battery-Operated **5210-P-14-AC** - 110-240 VAC

Not Shown:

5210-P-14-A-S4 - Model 5210-P-14-A with stainless steel collar for surface mounting.

5210-P-14-AC-S4 - Model 5210-P-14-AC with stainless steel collar for surface mounting.



