

Tubular Specialties Manufacturing, Inc.

13011 South Spring Street, Los Angeles, CA 90061-1685 Phone 800/CALL TSM (800/225-5876) or 310/515-4801 www.grabbar.com • Fax 310/217-0653


5230-SWH


Technical Data


Revised June 2004

Consult local codes to assure compliance

Surface Mounted Paper Towel Dispenser









Specification

Surface Mounted Paper Towel Dispenser shall be white enamel steel, welded. Door shall be drawn, one-piece seamless construction with no mitered corners; secured to cabinet with full-length piano hinge and tumbler lock. Refills shall be through concealed opening from bottom. Capacity shall be 400 C-fold or 525 multi-fold paper towels.

Surface Mounted Paper Towel Dispenser shall be Model 5230-SWH as manufactured by Tubular Specialties Manufacturing, 13011 South Spring Street, Los Angeles, California 90061, tel (800)Grab Bar.



Operation

Dispenses C-fold and multifold paper towels. Viewer slot indicates need for refill.



Materials/Workmanship

Cabinet White enamel steel, formed and welded. All exposed edges are ground smooth to eliminate burrs. Dispensing mouth has hemmed edge for safety. Capacity: 400 C-fold or 525 multi-fold paper towels.

Door Attached to cabinet body with full-length piano hinge.



Installation

- Unit is surface mounted on wall using screws provided by manufacturer as locations marked by an "S".
- 2. For plaster or dry wall, provide in-wall backing complying with local building codes.
- 3. For other surfaces, provide fiber plugs or expansion shields
- for use with screws provided by manufacturer, or provide toggle bolts or expansion bolts.
- 4. Recommended mounting height from finish floor to top of cabinet (not flange) is 66"-70" (1677-1778mm) standard and 54" (1372mm) for barrier-free design compliance.

