

Tubular Specialties Manufacturing, Inc.


13011 South Spring Street, Los Angeles, CA 90061-1685 Phone 800/CALL TSM (800/225-5876) or 310/515-4801 online www.grabbar.com • Fax 310/217-0653


Technical Data

Revised June 2001

Surface Mounted Paper Towel Dispenser









Suggested Architectural Specification

TSM Model 5230 Surface Mounted Paper Towel Dispenser from Tubular Specialties Manufacturing, Inc., Los Angeles, California, 310/515-4801 or 800/Call TSM (800/225-5876). Construction: Stainless steel type 304 (18-8) 22 gauge (0.8mm) satin finish, welded. Door: Drawn, one-piece seamless construction with no mitered corners; secured to cabinet with full-length stainless steel piano hinge and tumbler lock. Refills through concealed opening from bottom. Capacity: 400 C-fold or 500 multi-fold paper towels.



Operation

Dispenses C-fold and multifold paper towels. Viewer slot indicates need for refill.



Materials/Workmanship

Cabinet

Stainless steel type 304 (18-8) 22 gauge satin finish (0.8mm), formed and welded. All exposed edges are ground smooth to eliminate burrs. Dispensing mouth has hemmed edge for safety. Capacity: 400 C-fold or 500 multi-fold paper towels.

Stainless steel type 304 (18-8) 22 gauge. Attached to cabinet body with full-length stainless steel piano hinge.



Installation

Door

- 1. Unit is surface mounted on wall using screws provided by manufacturer as locations marked by an "S".
- 2. For plaster or dry wall, provide in-wall backing complying with local building codes.
- 3. For other surfaces, provide fiber plugs or expansion shields
- for use with screws provided by manufacturer, or provide toggle bolts or expansion bolts.
- 4. Recommended mounting height from finish floor to top of cabinet (not flange) is 66"-70" (1677-1778mm) standard and 54" (1372mm) for barrier-free design compliance.

