



Tubular Specialties Manufacturing, Inc.

13011 South Spring Street, Los Angeles, CA 90061-1685
 Phone 800/CALL TSM (800/225-5876) or 310/515-4801
 online www.grabbar.com • Fax 310/217-0653

CC-W

Wraparound Column Guard


Technical Data

Revised Oct. 2001

Page 1 of 2



Shown in Satin Finish St. St.



Model Numbers

CC-W Series Wraparound Column Guard, 60" Long

	SATIN FINISH ST. ST.	BRIGHT FINISH ST. ST.	BRIGHT FINISH BRASS	BRIGHT FINISH BRONZE	CLEAR ANODIZED ALUMINUM	
Column Cover I.D.	4 1/2"	CC-W60-4500/S	CC-W60-4500/B	CC-W60-4500/BB	CC-W60-4500/BBZ	CC-W60-4500/AA
	5"	CC-W60-5000/S	CC-W60-5000/B	CC-W60-5000/BB	CC-W60-5000/BBZ	CC-W60-5000/AA
	4 9/16"	CC-W60-5562/S	CC-W60-5562/B	CC-W60-5562/BB	CC-W60-5562/BBZ	CC-W60-5562/AA
	6"	CC-W60-6000/S	CC-W60-6000/B	CC-W60-6000/BB	CC-W60-6000/BBZ	CC-W60-6000/AA
	6 5/8"	CC-W60-6625/S	CC-W60-6625/B	CC-W60-6625/BB	CC-W60-6625/BBZ	CC-W60-6625/AA
	7 5/8"	CC-W60-7625/S	CC-W60-7625/B	CC-W60-7625/BB	CC-W60-7625/BBZ	CC-W60-7625/AA
	8"	CC-W60-8000/S	CC-W60-8000/B	CC-W60-8000/BB	CC-W60-8000/BBZ	CC-W60-8000/AA
	8 5/8"	CC-W60-8625/S	CC-W60-8625/B	CC-W60-8625/BB	CC-W60-8625/BBZ	CC-W60-8625/AA
	9 5/8"	CC-W60-9625/S	CC-W60-9625/B	CC-W60-9625/BB	CC-W60-9625/BBZ	CC-W60-9625/AA
	10 3/4"	CC-W60-1075/S	CC-W60-1075/B	CC-W60-1075/BB	CC-W60-1075/BBZ	CC-W60-1075/AA
	11 3/4"	CC-W60-1175/S	CC-W60-1175/B	CC-W60-1175/BB	CC-W60-1175/BBZ	CC-W60-1175/AA

Standard sizes shown at left.
 For custom sizes, please provide:

1. Column Diameter
2. Cover Height
3. Material Type
4. Thickness (gauge)
5. Finish

Please note the following:

- Minimum diameter 4" (102mm)
- Maximum length 72" (1829mm)
- Standard thickness for all metals is 24 gauge (.6mm)
- Maximum thickness for stainless steel is 18 gauge (1.2mm)
- Maximum thickness for brass, bronze and aluminum is 14 gauge (2.1mm)

CC-W Series Wraparound Column Guard, 72" Long

	SATIN FINISH ST. ST.	BRIGHT FINISH ST. ST.	BRIGHT FINISH BRASS	BRIGHT FINISH BRONZE	CLEAR ANODIZED ALUMINUM	
Column Cover I.D.	4 1/2"	CC-W72-4500/S	CC-W72-4500/B	CC-W72-4500/BB	CC-W72-4500/BBZ	CC-W72-4500/AA
	5"	CC-W72-5000/S	CC-W72-5000/B	CC-W72-5000/BB	CC-W72-5000/BBZ	CC-W72-5000/AA
	4 9/16"	CC-W72-5562/S	CC-W72-5562/B	CC-W72-5562/BB	CC-W72-5562/BBZ	CC-W72-5562/AA
	6"	CC-W72-6000/S	CC-W72-6000/B	CC-W72-6000/BB	CC-W72-6000/BBZ	CC-W72-6000/AA
	6 5/8"	CC-W72-6625/S	CC-W72-6625/B	CC-W72-6625/BB	CC-W72-6625/BBZ	CC-W72-6625/AA
	7 5/8"	CC-W72-7625/S	CC-W72-7625/B	CC-W72-7625/BB	CC-W72-7625/BBZ	CC-W72-7625/AA
	8"	CC-W72-8000/S	CC-W72-8000/B	CC-W72-8000/BB	CC-W72-8000/BBZ	CC-W72-8000/AA
	8 5/8"	CC-W72-8625/S	CC-W72-8625/B	CC-W72-8625/BB	CC-W72-8625/BBZ	CC-W72-8625/AA
	9 5/8"	CC-W72-9625/S	CC-W72-9625/B	CC-W72-9625/BB	CC-W72-9625/BBZ	CC-W72-9625/AA
	10 3/4"	CC-W72-1075/S	CC-W72-1075/B	CC-W72-1075/BB	CC-W72-1075/BBZ	CC-W72-1075/AA
	11 3/4"	CC-W72-1175/S	CC-W72-1175/B	CC-W72-1175/BB	CC-W72-1175/BBZ	CC-W72-1175/AA

Manufacturer reserves the right to alter design or dimensions without formal notice and without incurring obligation.

© 2001, Tubular Specialties Mfg., Inc. All Rights Reserved



Guarantee

TSM Column Guards are guaranteed against defects in workmanship and material for one year from shipping date.



Suggested Architectural Specification

TSM Model [Fill in Model Number]
 Wraparound Column Guard from Tubular
 Specialties Manufacturing, Inc., Los
 Angeles, California, 310/515-4801 or
 800/Call TSM (800/225-5876).
 Construction: One-piece formation with
 smooth edges. Material: 24 gauge (.6mm),
 [Stainless steel type 304, satin finish];

[Stainless steel type 304, bright finish];
 [Brass Alloy 260, bright finish]; [Bronze
 alloy 220, bright finish]; [Aluminum 6061,
 clear anodized finish]. PVC covered to
 protect finish during shipping and
 installation. Diameter: _____ (minimum
 4"). Height: [62" (1575mm)] [72"
 (1829mm)].



Materials

- | | |
|-------------------------------|---|
| Column Guard, St. St. | Stainless steel type 304, 24 gauge (.6mm), satin or bright finish. PVC covered to protect finish during shipment and installation. Alternate available: Type 430. |
| Column Guard, Brass | Brass alloy 260, 24 gauge (.6mm), bright finish. PVC covered to protect finish during shipment and installation. |
| Column Guard, Bronze | Bronze alloy 260, 24 gauge (.6mm), bright finish. PVC covered to protect finish during shipment and installation. |
| Column Guard, Aluminum | Aluminum 6061, 24 gauge (.6mm), clear anodized finish. PVC covered to protect finish during shipment and installation. |

Workmanship

- | | |
|------------------------|---|
| CC-W Wraparound | Overlapping hemmed edge that attaches to column with rivet or one-way screws (hardware provided by others). |
|------------------------|---|



Installation

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. Place column guard on the column with the hemmed edge overlapping the non-hemmed edge. 2. Tightly secure guard to the column by strapping the guard at each end and the center of the guard (strap provided by others). 3. Drill holes in the guard through the | <ol style="list-style-type: none"> overlapping edges maximum 12" apart and 1/2" from each end (305 & 13mm). 4. Secure by inserting pop rivets or screws (provided by others) into the drilled holes. 5. Remove straps and protective PVC covering. |
|--|---|