

TSM

TUBULAR SPECIALTIES MFG., INC.

13011 S. SPRING ST., LOS ANGELES, CA 90061-1685 • 213/515-4801 TOLL FREE 800/421-2961 CA ONLY 800/521-7548
DESIGNER SERVICE: 7:00 A.M. TO 5:00 P.M. PACIFIC TIME • TELEX II: 910-346-6362 • FAX: 213/217-0653

S-SH-60(15)

ECONOMY SHOWER CURTAIN ROD



DESIGN CONSIDERATIONS

- Shower curtain rods should not be specified in lieu of grab bars or any other support accessory.
- Shower curtains in vinyl, nylon and flame-resistant materials are also available from TSM to accompany its shower rods.



SUGGESTED ARCHITECTURAL SPECIFICATION

TSM model S-SH-60(15) Economy Shower Curtain Rod from Tubular Specialties Manufacturing, Inc., Los Angeles, California (213) 515-4801. Tubing: stainless steel Type 304 (18-8) 1" (25mm) x 28 gauge (0.4mm) x 60" (1524mm) with bright finish. Flanges: stainless steel Type 304 (18-8) 20 gauge (0.9mm), 3" (76mm) round, with exposed screws. Finish: bright polish. Installation Hardware: 2" (51mm) x #10 (5mm) stainless steel screws.



MATERIALS/WORKMANSHIP

Tubing—Stainless steel Type 304 (18-8) 28 gauge (0.4mm), lockseam (unwelded), bright finish, 1" (25mm) outside diameter. Standard length is 60" (1524mm); shorter lengths available.

Flanges (2)—Stainless steel Type 304 (18-8) 20 gauge (0.9mm). Each flange has two countersunk 3/16" (5mm) screw holes.



INSTALLATION

Surface mount flanges to wall at desired height (allow for standard shower curtain length of 72" [1829mm] plus approximately 1-1/2" [38mm] from top of curtain to centerline of rod). Screws are provided by manufacturer (see Installation, Reference Section C, for various applications).



DISTRIBUTION

TSM maintains a worldwide network of distributors. Call your sales representative listed in Reference Section O for the names of those nearest you.



GUARANTEED PRODUCT

SEE PAGE 3 FOR COMPLETE DETAILS

