



TSM corner guards help prevent damage to walls caused by carts and other wheeled vehicles. Besides being strong, they are attractive, economical, easy to install and will pay for themselves in reduced maintenance. They can also be used to cover existing wall damage.

TSM stainless steel corner guards are satin finish, 18 gauge type 430 and designed for indoor use (1.2mm). For exterior applications, specify type 304. Standard bend radius is 1/8" (3.2mm). All stainless steel corner guards are shipped with a PVC covering to protect their satin finish.

In addition to the models featured below, TSM encourages your requests for other sizes and configurations of corner guards, column covers and sheet metal items. We will be happy to discuss your requirements.

L-R: CP-3500 Series Corner Guard and EW End Wall Guard, a custom fabrication.


Surface-Mounted Stainless Steel Corner Guards

Although mastic is the standard installation for surface-mounted corner guards and is included with each order, screws are also available. Surface-mounted corner guards have slight hugger bends at each wing edge to accommodate imperfections in the surface of the wall.

See chart below for wing sizes and lengths; custom sizes readily available. 16 gauge is recommended for lengths over 60" (1.7,1524mm). The minimum custom wing size is 3/4" (19mm). Lengths over 120" will be made in two pieces (3048mm).

Model Numbers

Wings	Series	- Length -							
		40" (1016mm)	48" (1219mm)	60" (1524mm)	72" (1829mm)	84" (2134mm)	96" (2438mm)	108" (2743mm)	120" (3048mm)
1 1/2" x 1 1/2"	CP-1500 Series	CP-1540	CP-1548	CP-1560	CP-1572	CP-1584	CP-1596	CP-15108	CP-15120
2" x 2"	CP-2000 Series	CP-2040	CP-2048	CP-2060	CP-2072	CP-2084	CP-2096	CP-20108	CP-20120
2 1/2" x 2 1/2"	CP-2500 Series	CP-2540	CP-2548	CP-2560	CP-2572	CP-2584	CP-2596	CP-25108	CP-25120
3" x 3"	CP-3000 Series	CP-3040	CP-3048	CP-3060	CP-3072	CP-3084	CP-3096	CP-30108	CP-30120
3 1/2" x 3 1/2"	CP-3500 Series	CP-3540	CP-3548	CP-3560	CP-3572	CP-3584	CP-3596	CP-35108	CP-35120
EW Series									
End Wall Guard		Field Measure Web							
Wings & Webs Made to Order		Wings must be at least 3/4" (19mm) shorter than Web							



Options

Angle	Radius	Gauge	Material	Installation
90° Angle Standard	1/8" Radius Standard for CP and EW	18 gauge (.049") Standard	Type 430 Stainless Steel Standard	Mastic Standard
135° Angle Add suffix "@ 135°" to the model number	3/4" Radius Substitute "BN" (Bull Nose) for CP	16 gauge (.065") Add suffix "X" to the model number	Type 304 Stainless Steel Add suffix "T304" to the model #	Screws Add suffix "S" to the model number
		14 gauge (.083") Add suffix "XX" to the model number	Bright Brass with lacquered finish Add suffix "BB" to the model #	Countersunk Screws Add suffix "CSK" to the model number (available in 14 ga.

Column Covers

Column covers protect columns and provide a finished appearance. Minimum diameter 6" and maximum length 10' (152 & 3048mm):

CC-W Wraparound Cover

Overlapping hemmed edge attaches to column with rivet or one-way screws.



Shown in Satin Finish
Stainless Steel Model CC-WS

CC-C Clip Lock Cover

Outside clip slides down and locks column cover in place with no screws required.



Shown in Satin Finish
Stainless Steel Model CC-CS

Metal	Finish	Suffix
Stainless Steel Type 304	Satin	S
	Bright	B
Brass Alloy 260	Satin	BS
	Bright	BB
Aluminum 6061	Anodized	A
	Painted	AP
Bronze Alloy 220	Satin	BZA
	Bright	BZB