Shower Rod Tubing

Shower rod tubing is available in either stainless steel type 304 or brass alloy CDA 274 in a variety of diameters and gauges. To minimize scratches, fingerprints and watermarks, satin finish is recommended for either metal. Economy shower rods are available in bright mill finish aluminum.

Standard lengths of tubing for shower rods   *(custom lengths readily available)*

| 36" (914mm) | 48" (1219mm) | 72" (1829mm) | 96" (2438mm) |
| 42" (1067mm) | 60" (1524mm) | 84" (2134mm) | |

Stainless steel shower rods are available in satin or bright finish. The top rod features Q/CS-1 Series with 1¼" O.D. satin tubing and round concealed screw flanges, SC Nylon shower curtain in white and SC-HX stainless steel hooks. The bottom rod features S-1060/SH-1 Series with 1" O.D. bright finish slotted rod tubing with chrome plated steel hooks, exposed screw flanges and SCFR Flame-Resistant shower curtain in oatmeal.

Brass Shower Rod Tubing Model Numbers

Finish	18 ga. (1.2mm) Satin	18 ga. (1.2mm) Bright	20 ga. (.9mm) Satin	20 ga. (.9mm) Bright	28 ga. (.4mm) Bright TECH DATA	24 ga. (.6mm) Bright TECH DATA	16 ga. (1.7mm) Satin	16 ga. (1.7mm) Bright	18 ga. (1.2mm) Satin	18 ga. (1.2mm) Bright
Tubing Diameter 1"	S-106(49)	S-106(49)/B	S-106(35)	S-106(35)/B	S-106(15)/B Lockseam	S-1060(22)/B 60" Slotted Rod (hooks included)	S-106(62)/SB	S-106(62)/BB	S-106(49)/SB	S-106(49)/BB
1¼"	Q-106(49)	Q-106(49)/B	Q-106(35)	Q-106(35)/B	N/A	N/A	Q-106(62)/SB	Q-106(62)/BB	Q-106(49)/SB	Q-106(49)/BB

Stainless Steel Shower Rod Flanges

Base Plate = 14 gauge, Cover = 20 gauge (2.1 & .9mm) except where noted. Screws not included. Please see page 23 for fasteners.

TECH DATA

Round Exposed Screw
S-SH-1	- 1" Satin S/S
Q-SH-1	- 1¼" Satin S/S
S-SH-1/B	- 1" Bright S/S
Q-SH-1/B	- 1¼" Bright S/S

1" or 1¼"   20 ga.   3" (76mm)   ½" (6.4mm)

Neo-Angle Round Exposed Screw
S-SH-45	- 1" Satin S/S
Q-SH-45	- 1¼" Satin S/S
S-SH-45/B	- 1" Bright S/S
Q-SH-45/B	- 1¼" Bright S/S

1" or 1¼"   3"   45º   8 ga.

TECH DATA

Round Concealed Screw
S-CS-1	- 1" Satin S/S
Q-CS-1	- 1¼" Satin S/S
S-CS-1/B	- 1" Bright S/S
Q-CS-1/B	- 1¼" Bright S/S

1" or 1¼"   ½"   3" (76mm)

Rnd Concealed Screw w/ Sleeve
S-CS/SLEV	- 1" Satin S/S
Q-CS/SLEV	- 1¼" Satin S/S
S-CS/SLEV/B	- 1" Bright S/S
Q-CS/SLEV/B	- 1¼" Bright S/S

1" or 1¼"   3" (76mm)   2"   S = 1¼" x .109"   Q = 1½" x .109"

TECH DATA

Square Concealed Screw
S-FS-1	- 1" Satin S/S
Q-FS-1	- 1¼" Satin S/S
S-FS-1/B	- 1" Bright S/S
Q-FS-1/B	- 1¼" Bright S/S

1" or 1¼"   1" or 1¼"   2½" (64mm)   2½"   3/8" (9.5mm)

Round Concealed Screw
Internally threaded sleeve screws onto the base that is attached to wall. Set screw on one end.

S-SH-2   -   1"   Satin Chrome Brass

1¼" (32 mm)   S   5/8" (16 mm)

Brass Shower Rod Flanges

Base Plate = 14 gauge, Cover = 20 gauge (2.1 & .9 mm) except where noted.

Round Concealed Screw
S-CS-1/SB	- 1" Satin
Q-CS-1/SB	- 1¼" Satin
S-CS-1/BB	- 1" Bright
S-CS-1/BB	- 1" Bright

1" or 1¼"   ½"   3"

Round Concealed Screw with Sleeve
S-CS-SLEV/PLSB	- 1" Plated Satin
Q-CS-SLEV/PLSB	- 1¼" Plated Satin
S-CS-SLEV/PLBB	- 1" Plated Bright
S-CS-SLEV/PLBB	- 1" Plated Bright

1" or 1¼"   3" (76mm)   2"   S = 1¼" x .109"   Q = 1½" x .109"

Economy Shower Rods

Adjustable Twist-In Flange
No screws necessary to install. Twists clockwise to tighten to wall.

S-SH-5/Z -   1"   Bright Chrome Zamac

S-SH-5/P -   1"   Bright Chrome Plastic

1"   1⅜" (35 mm)   1 11/16" (43 mm)   1¾"   ¾" (19 mm)

Aluminum Shower Rod Tubing
1" x .015 (28 ga.) Bright Mill Finish
S-106(15)/A @ 60"
S-106(15)/A @ 72"

Ceiling Supports and 90° Shower Rods

Type 304 stainless steel is standard; add suffix /B for bright stainless, /BB for bright brass and /SB for satin brass. Recommended for any shower rod length over 60".

C-7
Sleeve Ceiling Support
S-C-7 - 1" Dia.
Q-C-7 - 1¼" Dia.

Recommended for rods over 60". Standard height is 12"; custom heights available. Requires two shower curtains. Movable sleeve fits over shower rod tubing. Concealed screw CS-1 flange, all welded construction. Satin finish is standard; add suffix /B for bright finish. Not available in brass.

S-C-7/B

C-8
"J" Ceiling Support
S-C-8 - 1" Dia.

Recommended for rods over 60". Standard height is 12"; custom heights available. Allows one shower curtain to be used, but only with PC-HX hooks. Available for 1" tubing only (25mm). Saddle attaches to shower rod with two set screws. For stainless steel, diamond-shaped 14 gauge flange is welded to ¼" rod (2.1 x 6.4 mm). For brass, rectangular 12 gauge flange is welded to ¼" rod (2.8 x 6.4 mm).

3060/C-7
Corner Shower Curtain Rod with Sleeve Ceiling Support
S-3060/C-7 - 1" Dia.   TECH DATA
Q-3060/C-7 - 1¼" Dia.

Movable ceiling support with sleeve requires two shower curtains. Includes welded CS-1 at each end and ceiling. Modifications of all kinds are available from the basic 30" x 60" design (762x1524mm), including different dimensions for legs or ceiling height, custom radii, etc.

S-3060/C-7 with SC nylon curtains in red.

3060/C-8
Corner Shower Curtain Rod with "J" Ceiling Support
S-3060/C-8 - 1" Dia.

Same as 3060/C-7 except under-slung ceiling support is welded to tubing, allowing one shower curtain to be used (requires PC-HX hooks). Shipped in components to prevent damage in transit.

Patent Pending

S-3060/C-8/BB with SC nylon curtain in navy.

Shower Curtains and Hooks

TSM curtains are available in three materials: Vinyl, Flame-Resistant and Nylon. Custom widths and heights are available. Specify curtains from 6" to 12" (152-305mm) wider than curtain rod. White is standard. Weights are sewn into the bottom hem of the nylon curtains *(not necessary for vinyl or flame-resistant.)*

Width	Height	Hooks Required
36"	x 72"	7
42"	x 72"	8
48"	x 72"	9
60"	x 72"	11
72"	x 72"	13
84"	x 72"	15

SCV   TECH DATA
Vinyl Curtain
Vinyl film .008 mil. Anti-bacterial and flame-retardant. White (standard), Translucent and Almond.

SCV-36	- 36" x 72"
SCV-42	- 42" x 72"
SCV-48	- 48" x 72"
SCV-60	- 60" x 72"
SCV-72	- 72" x 72"
SCV-84	- 84" x 72"

SCFR   TECH DATA
Flame-Resistant Curtain
Vinyl-laminated fiberglass with flame, static, bacteria and mildew resistance. White (standard), Oatmeal and Arabian Beige.

SCFR-36	- 36" x 72"
SCFR-42	- 42" x 72"
SCFR-48	- 48" x 72"
SCFR-60	- 60" x 72"
SCFR-72	- 72" x 72"
SCFR-84	- 84" x 72"

SC   TECH DATA
Nylon Curtain
Nylon shell cloth 150 denier. White (standard), Maize, Gold, Orange, Red, Hunter Green, Royal Blue and Black.

SC-36	- 36" x 72"
SC-42	- 42" x 72"
SC-48	- 48" x 72"
SC-60	- 60" x 72"
SC-72	- 72" x 72"
SC-84	- 84" x 72"

SC-HX   TECH DATA
Stainless Steel
Type 304 stainless steel wire, satin finish.

Fits 1" or 1¼" O.D.

PC-HX   TECH DATA
Plastic
Pear-shaped polystyrene hook.
White (standard), Clear, Wheat, Navy, Slate Blue, Forest Green, Maroon and Black.

Fits 1" O.D.

PC-HX-R   TECH DATA
Plastic
Same as PC-HX except round.
White (standard), Clear, Almond, Light Blue, Slate Blue, Dark Blue, Seafoam Green, Forest Green, Pink, Rose, Raspberry, Maroon, Melon and Black.

Fits 1" or 1¼" O.D.